

# MI890

Intel® Pineview-M/ Pineview-D +ICH8M  
Luna-Pier / Luna-Pier Refresh Platform  
Mini-ITX Motherboard

## USER'S MANUAL

Version 1.0

---

## Acknowledgments

AMI BIOS is a trademark of American Megatrends Inc.

PS/2 is a trademark of International Business Machines Corporation.

Intel and Atom are registered trademarks of Intel Corporation.

Microsoft Windows is a registered trademark of Microsoft Corporation.

Winbond is a registered trademark of Winbond Electronics Corporation.

All other product names or trademarks are properties of their respective owners.

---

# Table of Contents

<b>Introduction .....</b>	<b>1</b>
Checklist.....	2
MI890 Specifications .....	3
Board Dimensions .....	4
<b>Installations .....</b>	<b>5</b>
Setting the Jumpers .....	6
Connectors on MI890.....	10
<b>BIOS SETUP .....</b>	<b>17</b>
<b>Drivers Installation .....</b>	<b>37</b>
<b>Appendix .....</b>	<b>45</b>
A. I/O Port Address Map.....	45
B. Interrupt Request Lines (IRQ).....	48
C. Watchdog Timer Configuration.....	49
D. Digital I/O Sample Code .....	54

---

This page is intentionally left blank.

# Introduction



MI890 MINI ITX MOTHERBOARD



MI890 EDGE CONNECTORS

## **Checklist**

---


Your MI890 package should include the items listed below.

- The MI890 Intel® Atom Mini-ITX motherboard
- This User's Manual
- 1 CD containing chipset drivers and flash memory utility
- Cables (IDE cable, Serial ATA cable)

## MI890 Specifications

<b>Product Name</b>	<b>MI890-N4/ MI890-D4 / MI890-D5</b>
<b>Form Factor</b>	MiniITX
<b>CPU Type</b>	Intel® Atom™ SC N455 (512KB L2 cache, 1 Core/ 2 Threads. TDP=6.5W) Intel® Atom™ SC D425 (512KB L2 cache, 1 Core/ 2 Threads. TDP=10W) Intel® Atom™ DC D525 (1MB L2 cache, 2 Core/ 2 Threads. TDP=13W) 22mm x 22mm, Micro-FCBGA8
<b>CPU Speed</b>	<b>1.66GHz (N455) / 1.80GHz(D425/D525)</b>
<b>Chipset</b>	ICH8M: 31mm x 31mm, 676-pin T-PBGA (2.4W)
<b>BIOS</b>	AMI BIOS
<b>Memory</b>	DDR3-800 (Single channel) SO-DIMM x2 (Non-ECC), Max.= 2GB(N455) / 4GB(D425/D525)
<b>VGA</b>	Intel® Integrated Graphics Controller Supports DirectX 9 Graphic (200MHz for N455 ; 400MHz for D425/D525) OpenGL 1.4
<b>LVDS</b>	18-bit one channels LVDS interface w/DF13 socket x1
<b>LAN</b>	Intel 82583V x 2 for Dual GbE
<b>USB</b>	ICH8M built-in USB 2.0 host controller, support 9 ports
<b>Serial ATA Ports</b>	ICH8M built-in SATA controller, supports 2 ports
<b>Parallel IDE</b>	ICH8M built-in one channel Ultra DMA 33/66/100, for CF Type II (Component side)
<b>Audio</b>	Intel ICH8M built-in HD audio controller w/ Realtek ALC269 Codec with integrated 2W amplifier (4 Ohm) Supports 2 Channel audio (Line-out & Line-in )
<b>LPC I/O</b>	Winbond NCT6627UD : COM1 (RS232/422/485), COM2~COM4(RS232) with pin-9 with power for 2 ports (500 mA for each port) [COM3/4] Hardware monitor (2 thermal inputs, 4 voltage monitor inputs, VIDO-4 & 1 x fan header)
<b>Digital IO</b>	4 in & 4 out
<b>Expansion Slots</b>	Mini PCI-e x 1 w/USB for WiFi or TV-tuner module (Reserved screw holes for half-mini type also) PCI slot x 1 + PCI-Express(1x) slot x1
<b>Edge Connector</b>	DC-Jack x 1 DB15 connector x1 for VGA Dual DB9 Stack connector x 1 for COM1/ COM2 RJ45 + Dual USB stack connector x1 for LAN 1 + USB 1/2 RJ45 + Dual USB stack connector x1 for LAN 2 + USB 3/4 Audio 3-port connector x 1 (Line-out , Line-in& Mic)
<b>On Board Header/Connector</b>	2x4 pin header x2 for 4 USB ports DF13 socket x 1 for LVDS( 18-bit single channel) DF11 socket 20-pin connector x 1 for COM3, COM4 CF type II connector x1 SATA II connector x2 2x5 pin header x1 for Digital I/O 2x6 pin header x1 for front audio 4-pin header x2 for SATA power (Mini type)
<b>Watchdog Timer</b>	Yes (256 segments, 0, 1, 2...255 sec/min)
<b>Others</b>	Optional EuP feature (Fintek F75160) UL 60950-1 2 <sup>nd</sup> Edition compatible
<b>Power Connector</b>	12V ~ 24V DC-in
<b>Board Size</b>	170mm x 170mm

# Board Dimensions



## Installations

This section provides information on how to use the jumpers and connectors on the MI890 in order to set up a workable system. The topics covered are:

Setting the Jumpers.....	6
Connectors on MI890.....	10

## Setting the Jumpers


---

---

Jumpers are used on MI890 to select various settings and features according to your needs and applications. Contact your supplier if you have doubts about the best configuration for your needs. The following lists the connectors on MI890 and their respective functions.



Jumper Locations on MI890 .....	7
JP1: LCD Panel Power Selection.....	8
JP3, JP4, JP5: RS232/422/485 (COM1) Selection .....	8
JP7, JP9: COM4 RS232 RI/+5V/+12V Power Setting.....	8
JP11: Clear CMOS Setting .....	8
JP12, JP14: ATX / AT Mode Select Setting.....	9
JP15: EuP Control (option).....	9
JP13: +3VS For ID381 .....	9
JP16: +5VS For ID381 .....	9

**Jumper Locations on MI890**




Jumper Locations on MI890.....	7
JP1: LCD Panel Power Selection .....	8
JP3, JP4, JP5: RS232/422/485 (COM1) Selection .....	8
JP7, JP9: COM4 RS232 RI/+5V/+12V Power Setting.....	8
JP11: Clear CMOS Setting .....	8
JP12, JP14: ATX / AT Mode Select Setting .....	9
JP15: EuP Control (option) .....	9
JP13: +3VS For ID381 .....	9
JP16: +5VS For ID381 .....	9

**JP1: LCD Panel Power Selection**


JP1	LCD Panel Power
 1 2 3	3.3V
 1 2 3	5V

**JP3, JP4, JP5: RS232/422/485 (COM1) Selection**





COM1 Function	RS-232	RS-422	RS-485
Jumper Setting (pin closed)	JP5: 1-2	JP5: 3-4	JP5: 5-6
	JP3: 3-5 & 4-6	JP3: 1-3 & 2-4	JP3: 1-3 & 2-4
	JP4: 3-5 & 4-6	JP4: 1-3 & 2-4	JP4: 1-3 & 2-4



**JP7, JP9: COM4 RS232 RI/+5V/+12V Power Setting**

JP7/JP9	Setting	Function
	Pin 1-2 Short/Closed	+12V
	Pin 3-4 Short/Closed	RI
	Pin 5-6 Short/Closed	+5V



**JP11: Clear CMOS Setting**

JP11	Function
 1 2 3	Normal
 1 2 3	Clear CMOS

**JP12, JP14: ATX / AT Mode Select Setting**

JP12 / JP14	Setting	Function
	JP12 1-2, JP14 open	ATX Mode
	JP12 2-3, JP14 short	AT Mode

**JP15: EuP Control (option)**

JP15	Setting	Function
	Pin 1-2 Short/Closed	Normal On <b>Default</b>
	Pin 2-3 Short/Closed	EuP Off


**JP13: +3VS For ID381****JP16: +5VS For ID381**

## Connectors on MI890

The connectors on MI890 allows you to connect external devices such as keyboard, floppy disk drives, hard disk drives, printers, etc. The following table lists the connectors on MI890 and their respective functions.


Connector Locations on MI890 .....	11
J17: DC_IN Jack (+12V~24V).....	12
CN2: VGA Connector .....	12
CN3: COM1 and COM2 Serial Port Connectors.....	12
CN6: 10/100/1000 RJ-45 and USB1/2 Ports .....	13
CN9:10/100/1000 RJ-45 and USB3/4Ports .....	13
CN10: Line-in, Line-out & Microphone Connector .....	13
CPU_FAN1 : CPU Fan Power Connector (DC Fan).....	13
J1: LCD Backlight Connector.....	13
J3 : LVDS Connectors (18-bit).....	13
J4: DC_IN Connector .....	14
J5: Digital I/O .....	14
J8: Power LED Connector .....	14
J9: System Function Connector .....	14
J10: SPI Flash Connector (factory use only) .....	14
J12: USB5/USB6 Connector .....	15
J13: USB7/USB8 Connector .....	15
J14: Compact Flash Connector .....	15
J15: Audio Connector (DF11 Connector).....	15
J16: Mini PCIE Connector.....	15
J18: PS/2 Keyboard and PS/2 Mouse Connectors .....	15
J19/J20: SATA Power Output .....	15
J21: Audio Amplifier.....	15
CN4/CN5: SATA Connectors .....	15
J24: Smart Battery Connector (option).....	16
ID381 LVDS Daughter Card.....	16
J1: LVDS 24bit Output.....	16
J2: LVDS Input from MI890 .....	16
CN1: DVI-I Output.....	16





**J17: DC\_IN Jack (+12V~24V)**


**CN2: VGA Connector**



**VGA**


Signal Name	Pin #	Pin #	Signal Name
Red	1	2	Green
Blue	3	4	N.C.
GND	5	6	GND
GND	7	8	GND
N.C.	9	10	GND
N.C.	11	12	N.C.
HSYNC	13	14	VSYNC
NC	15		

**CN3: COM1 and COM2 Serial Port Connectors**




**COM2**

Signal Name	Pin #	Pin #	Signal Name
DCD	1	6	DSR
RXD	2	7	RTS
TXD	3	8	CTS
DTR	4	9	RI
GND	5	10	Not Used



**COM1**

Pin #	Signal Name		
	RS-232	R2-422	RS-485
1	DCD	TX-	DATA-
2	RX	TX+	DATA+
3	TX	RX+	NC
4	DTR	RX-	NC
5	Ground	Ground	Ground
6	DSR	NC	NC
7	RTS	NC	NC
8	CTS	NC	NC
9	RI	NC	NC
10	NC	NC	NC



**CN6: 10/100/1000 RJ-45 and USB1/2 Ports**

**CN9:10/100/1000 RJ-45 and USB3/4Ports**

**CN10: Line-in, Line-out & Microphone Connector**

**CPU\_FAN1 : CPU Fan Power Connector (DC Fan)**




Pin #	Signal Name
1	Ground
2	+12V
3	Rotation detection

**J1: LCD Backlight Connector**



Pin #	Signal Name
1	+12V
2	Backlight Enable
3	Brightness Control
4	Ground

**J3 : LVDS Connectors (18-bit)**




Signal Name	Pin #	Pin #	Signal Name
TX0-	2	1	TX0+
Ground	4	3	Ground
TX1-	6	5	TX1+
5V/3.3V	8	7	Ground
NC	10	9	NC
TX2-	12	11	TX2+
Ground	14	13	Ground
TXC-	16	15	TXC+
5V/3.3V	18	17	ENABKL
+12V	20	19	+12V

**J4: DC\_IN Connector**


Note: J4 input voltage is +12V only.

**J5: Digital I/O**



Signal Name	Pin	Pin	Signal Name
OUT3	1	2	VCC
OUT2	3	4	OUT1
GND	5	6	OUT0
IN3	7	8	IN1
IN2	9	10	IN0

**J6: COM3/ COM4 RS232 Serial Ports (option)**




Signal Name	Pin #	Pin #	Signal Name
DSR1	2	1	DCD1
RTS1	4	3	RXD1
CTS1	6	5	TXD1
RI1	8	7	DTR1
NA	10	9	Ground
DSR2	12	11	DCD2
RTS2	14	13	RXD2
CTS2	16	15	TXD2
RI2	18	17	DTR2
NA	20	19	Ground

**J8: Power LED Connector**




Pin #	Signal Name
1	+5V
2	NC
3	Ground

**J9: System Function Connector**




**J10: SPI Flash Connector (factory use only)**

**J12: USB5/USB6 Connector**



Signal Name	Pin	Pin	Signal Name
Vcc	1	2	Ground
D-	3	4	D+
D+	5	6	D-
Ground	7	8	Vcc


**J13: USB7/USB8 Connector**



Signal Name	Pin	Pin	Signal Name
Vcc	1	2	Ground
D-	3	4	D+
D+	5	6	D-
Ground	7	8	Vcc

**J14: Compact Flash Connector**

**J15: Audio Connector (DF11 Connector)**




Signal Name	Pin #	Pin #	Signal Name
LINEOUT R	2	1	LINEOUT L
Ground	4	3	JD FRONT
LINEIN R	6	5	LINEIN L
Ground	8	7	JD LINEIN
MIC-In	10	9	MIC L
Ground	12	11	JD MIC1

**J16: Mini PCIE Connector**

**J18: PS/2 Keyboard and PS/2 Mouse Connectors**

*Remarks: For testing use only.*



Signal Name	Pin	Pin	Signal Name
Vcc	1	2	VCC
MDA	3	4	KBDA
MCL	5	6	KBCL
Ground	7	8	Ground


**J191/J201: SATA Power Output**

**J21: Audio Amplifier**

**CN4/CN5: SATA Connectors**


**J24: Smart Battery Connector (option)**

Pin #	Signal Name
1	PCIRST-
2	EMTSMI-
3	Ground
4	SMBDATA
5	SMBCLK



**ID381 LVDS Daughter Card**

The ID381 card supports 24-bit LVDS and DVI interface.



**J1: LVDS 24bit Output**

**J2: LVDS Input from MI890**

**CN1: DVI-I Output**

---

## BIOS SETUP

This chapter describes the different settings available in the AMI (American Megatrends, Inc.) BIOS that comes with the board. The topics covered in this chapter are as follows:

BIOS Introduction .....	18
BIOS Setup .....	18
Main BIOS Setup .....	19
Advanced Settings .....	20
PCIPnP Settings .....	28
Boot Settings .....	29
Security Settings .....	31
Advanced Chipset Settings .....	32
Exit Setup .....	35
Load Optimal Defaults .....	35
Load Failsafe Defaults .....	35

## BIOS Introduction

The BIOS (Basic Input/Output System) installed in your computer system's ROM supports Intel processors. The BIOS provides critical low-level support for a standard device such as disk drives, serial ports and parallel ports. It also adds virus and password protection as well as special support for detailed fine-tuning of the chipset controlling the entire system.

## BIOS Setup

The BIOS provides a Setup utility program for specifying the system configurations and settings. The BIOS ROM of the system stores the Setup utility. When you turn on the computer, the BIOS is immediately activated. Pressing the <Del> key immediately allows you to enter the Setup utility. If you are a little bit late pressing the <Del> key, POST (Power On Self Test) will continue with its test routines, thus preventing you from invoking the Setup. If you still wish to enter Setup, restart the system by pressing the "Reset" button or simultaneously pressing the <Ctrl>, <Alt> and <Delete> keys. You can also restart by turning the system Off and back On again. The following message will appear on the screen:

Press <DEL> to Enter Setup

In general, you press the arrow keys to highlight items, <Enter> to select, the <PgUp> and <PgDn> keys to change entries, <F1> for help and <Esc> to quit.

When you enter the Setup utility, the Main Menu screen will appear on the screen. The Main Menu allows you to select from various setup functions and exit choices.

## Main BIOS Setup

This setup allows you to record some basic hardware configurations in your computer system and set the system clock.


BIOS SETUP UTILITY						
Main	Advanced	PCIPnP	Boot	Security	Chipset	Exit
<b>System Overview</b>				Use[ENTER], [TAB] or [SHIFT-TAB] to select a field.		
<b>Processor</b>				Use [+] or [-] to configure system Time.		
Intel(R) Atom (TM) CPU D525		@ 1.80GHz				
Speed : 1800MHz						
Count : 1						
<b>System Memory</b>				<- Select Screen		
Size : 2038MB				↑↓ Select Item		
<b>System Time</b>				+- Change Field		
System Date		[17:00:00]		Tab Select Field		
		[Tue 05/25/2010]		F1 General Help		
				F10 Save and Exit		
				ESC Exit		

**Note:** *If the system cannot boot after making and saving system changes with Setup, the AMI BIOS supports an override to the CMOS settings that resets your system to its default.*

**Warning:** *It is strongly recommended that you avoid making any changes to the chipset defaults. These defaults have been carefully chosen by both AMI and your system manufacturer to provide the absolute maximum performance and reliability. Changing the defaults could cause the system to become unstable and crash in some cases.*

## Advanced Settings

This section allows you to configure and improve your system and allows you to set up some system features according to your preference.



The Advanced BIOS Settings contains the following sections:

- ▶ CPU Configurations
- ▶ IDE Configuration
- ▶ Super IO Configuration
- ▶ Hardware Health Configuration
- ▶ ACPI Configuration
- ▶ AHCI Configuration
- ▶ APM Configuration
- ▶ USB Configuration

The fields in each section are shown in the following pages, as seen in the computer screen. Please note that setting the wrong values may cause the system to malfunction. If unsure, please contact technical support of your supplier.

## BIOS SETUP UTILITY

Advanced	
<b>Configure advanced CPU settings</b>	
Module Version:3F.18	
Manufacturer: Intel	
Intel(R) Atom (TM) CPU D525	@ 1.80GHz
Frequency : 1.80GHz	
FSB Speed : 800MHz	
Cache L1 : 48KB	
Cache L2 : 1024KB	
Ratio Actual Value : 9	
<b>Max CPUID Value Limit</b>	[Disabled]
Execute-Disable Bit Capability	[Enabled]
Hyper Threading Technology	[Enabled]
Disabled for WindowsXP  <- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit	

The CPU Configuration menu shows the following CPU details: Manufacturer: the name of the CPU manufacturer

Brand String: the brand name of the CPU being used

Frequency: the CPU processing speed

FSB Speed: the FSB speed

Cache L1: the CPU L1 cache size

Cache L2: the CPU L2 cache

### Max CPUID Value Limit

Disabled for WindowsXP.

### Execute-Disable Bit Capability

XD can prevent certain classes of malicious buffer overflow attacks when combined with a supporting OS.

### Hyper Threading Technology

Enabled for Windows XP and Linux (OS optimized for Hyper-Threading Technology) and Disabled for other OS (OS not optimized for Hyper-Threading Technology). When Disabled, only one thread per enabled core is enabled.

BIOS SETUP UTILITY

Advanced		Options
<b>IDE Configuration</b>		Disabled Compatible Enhanced  <- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
<b>ATA/IDE Configuration</b> Configure SATA as [Enhanced] [IDE]		
▶ Primary IDE Master : [Not Detected] ▶ Primary IDE Slave : [Not Detected] ▶ Secondary IDE Master : [Not Detected] ▶ Secondary IDE Slave : [Not Detected] ▶ Third IDE Master : [Not Detected] ▶ Third IDE Slave : [Not Detected] ▶ Fourth IDE Master : [Not Detected] ▶ Fourth IDE Slave : [Not Detected]		
Hard Disk Write Protect [Disabled] IDE Detect Time Out (Sec) [35] ATA(Pi) 80Pin Cable Detection [Host & Device]		

The IDE Configuration menu is used to change and/or set the configuration of the IDE devices installed in the system.

### ATA/IDE Configuration

- (1) Disabled.
- (2) Compatible.
- (3) Enhanced

### Configure SATA as

- (1) IDE Mode.
- (2) AHCI Mode.

BIOS SETUP UTILITY

Advanced		Options
<b>Configure Win627UHG Super IO Chipset</b>		Allows BIOS to Select Serial Port Base Addresses  <- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
<b>Serial Port1 Address</b> [3F8/IRQ4] Serial Port2 Address [2F8/IRQ3] Serial Port3 Address [3E8] Serial PortC IRQ [IRQ11] Serial Port4 Address [2E8] Serial PortD IRQ [IRQ10] Restore on AC Power Loss [Power Off] COM1 RS485 Auto Flow Control [Disabled]		

## Onboard Serial Port

The default values are:

- Serial Port 1: 3F8/IRQ4
- Serial Port 2: 2F8/IRQ3
- Serial Port 3: 3E8/IRQ11
- Serial Port 4: 2E8/IRQ10

## Restore on AC Power Loss

This field sets the system power status whether *Power On* or *Power Off* when power returns to the system from a power failure situation.

### BIOS SETUP UTILITY

Advanced		Options
<b>Hardware Health Configuration</b>		
System Temperature	:42°C/107°F	<b>Disabled</b>
CPU Temperature	:37°C/98°F	<b>70°C/158°F</b>
CPU FAN Speed	:6750 RPM	<b>75°C/167°F</b>
Vcore	:1.136 V	<b>80°C/176°F</b>
+5VS	:5.304 V	<b>85°C/185°F</b>
+3VS	:3.200 V	<b>90°C/194°F</b>
12 V	:11.904 V	<b>95°C/203°F</b>
3.3V	:3.408 V	
1.5V	:1.504V	<- Select Screen
VBAT	: 3.536V	↑↓ Select Item
CPU Smart Fan	[Disabled]	+ - Change Option
ACPI Shutdown Temperature	[Disabled]	Tab Select Field
		F1 General Help
		F10 Save and Exit
		ESC Exit

The Hardware Health Configuration menu is used to show the operating temperature, fan speeds and system voltages.

## ACPI Shutdown Temperature

The system will shut down automatically under OS with ACPI mode, when the CPU temperature reaches the configured temperature.

BIOS SETUP UTILITY

Advanced	
<b>ACPI Settings</b>	<b>General ACPI Configuration settings</b>
<ul style="list-style-type: none"> <li>▶ General ACPI Configuration</li> <li>▶ Advanced ACPI Configuration</li> <li>▶ Chipset ACPI Configuration</li> </ul>	<p>&lt;- Select Screen                      ↑↓ Select Item                      Enter Go to Sub Screen                      F1 General Help                      F10 Save and Exit                      ESC Exit</p>

BIOS SETUP UTILITY

Advanced	
<b>General ACPI Configuration</b>	<b>Select the ACPI state used for System Suspend.</b>
Suspend mode [S1 (POS)]	<p>&lt;- Select Screen                      ↑↓ Select Item                      +- Change Option                      F1 General Help                      F10 Save and Exit                      ESC Exit</p>

**Suspend Mode**

The options of this field are *S1*, *S3* and *Auto*.

BIOS SETUP UTILITY

Advanced	
<b>Advance ACPI Configuration</b>	<b>Enable RSDP pointers to 64-bit Fixed System Description Tables. Different ACPI version Has some addition</b>
ACPI Version Features [ACPI v1.0] ACPI APIC support [Enabled]	<p>&lt;- Select Screen                      ↑↓ Select Item                      +- Change Option                      F1 General Help                      F10 Save and Exit                      ESC Exit</p>

## BIOS SETUP UTILITY

Advanced	
<b>South Bridge ACPI Configuration</b>	<b>Options</b>
Energy Lake Feature [Disabled]	Enabled Disabled
APIC ACPI SCI IRQ [Disabled]	
USB Device Wakeup From S3/S4 [Disabled]	
	<- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit

## BIOS SETUP UTILITY

Advanced	
<b>AHCI Settings</b>	<b>While entering setup, BIOS auto detect the presence of IDE device. This displays the status of auto detection of IDE devices.</b>
AHCI Port0 [Not Detected]	
AHCI Port1 [Not Detected]	
AHCI Port2 [Not Detected]	
	<- Select Screen ↑↓ Select Item Enter Go to Sub Screen F1 General Help F10 Save and Exit ESC Exit

## BIOS SETUP UTILITY

Advanced	
<b>APM Configuration</b>	<b>Enable or disable APM.</b>
<b>Power Management/APM</b> [Enabled]	
Power Button Mode [On/Off]	
Resume On Ring Disabled	
Resume On PME# Disabled	<- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
Resume On RTC Alarm Disabled	

### **Power Management/APM**

By default, this field is set to *Enabled*.

### **Power Button Mode**

Go into On/Off, or Suspend when power button is pressed.

### **Resume on Ring**

This option is used to enable activity on the RI (ring in) modem line to wake up the system from a suspend or standby state. That is, the system will be awakened by an incoming call on a modem.

### **Resume on PME#**

This option is used enable activity on the PCI PME (power management event) controller to wake up the system from a suspend or standby state

### **Resume On RTC Alarm**

This option is used to specify the time the system should be awakened from a suspended state

## BIOS SETUP UTILITY

Advanced	
<b>USB Configuration</b>	Enables support for legacy USB. AUTO option disables legacy support if no USB devices are connected.
<b>USB Devices Enabled:</b> None	
<b>Legacy USB Support</b> [Enabled] USB 2.0 Controller Mode [HiSpeed] BIOS EHCI Hand-Off [Enabled] Legacy USB1.1 HC Support [Enabled]	<- Select Screen ↑↓ Select Item +/- Change Option F1 General Help F10 Save and Exit ESC Exit

The USB Configuration menu is used to read USB configuration information and configure the USB settings.

### Legacy USB Support

Enables support for legacy USB. AUTO option disables legacy support if no USB devices are connected.

### USB 2.0 Controller Mode

Configures the USB 2.0 controller in HiSpeed (480Mbps) or FullSpeed (12Mbps). This option is enabled by HiSpeed.

### BIOS EHCI Hand-Off

Enabled/Disabled. This is a workaround for Oses without EHCI hand-off support. The EHCI ownership change should be claimed by EHCI driver.

### Legacy USB1.1 HC Support

Support USB1.1 HC.

## PCIPnP Settings

This option configures the PCI/PnP settings.

BIOS SETUP UTILITY			
Main	Advanced	PCIPnP	Boot Security Chipset Exit
<b>Advanced PCI/PnP Settings</b>			
<b>WARNING: Setting wrong values in below sections may cause system to malfunction.</b>			
<b>Plug &amp; Play O/S</b>		[No]	
Allocate IRQ to PCI VGA		[Yes]	
IRQ3		[Available]	
IRQ4		[Available]	
IRQ5		[Available]	
IRQ7		[Available]	
IRQ9		[Available]	
IRQ10		[Available]	
IRQ11		[Available]	
IRQ14		[Available]	
IRQ15		[Available]	
DMA Channel 0		[Available]	
DMA Channel 1		[Available]	
DMA Channel 3		[Available]	
DMA Channel 5		[Available]	
DMA Channel 6		[Available]	
DMA Channel 7		[Available]	
Reserved Memory Size		[Disabled]	
		NO: lets the BIOS Configure all the Devices in the system. YES: lets the operating system configure Plug and Play (PnP) devices not required for boot if your system has a Plug and Play operating system.	
		<- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit	

### Plug & Play O/S

This lets BIOS configure all devices in the system or lets the OS configure PnP devices not required for boot if your system has a Plug and Play OS.

### Allocate IRQ to PCI VGA

This assigns IRQ to PCI VGA card if card requests IRQ or doesn't assign IRQ to PCI VGA card even if card requests an IRQ.

### IRQ#

Use the IRQ# address to specify what IRQs can be assigned to a particular peripheral device.

## Boot Settings

BIOS SETUP UTILITY						
Main	Advanced	PCI/PnP	Boot	Security	Chipset	Exit
<b>Boot Settings</b>			Configure Settings during System Boot.			
▶ Boot Settings Configuration			<- Select Screen ↑↓ Select Item Enter Go to Sub Screen F1 General Help F10 Save and Exit ESC Exit			

BIOS SETUP UTILITY	
Boot	
<b>Boot Settings Configuration</b>	
<b>Quick Boot</b> [Enabled] Quiet Boot [Disabled] AddOn ROM Display Mode [Force BIOS] Bootup Num-Lock [On] PS/2 Mouse Support [Auto] Wait for 'F1' If Error [Enabled] Hit 'DEL' Message Display [Enabled] Interrupt 19 Capture [Disabled]	Allows BIOS to skip certain tests while booting. This will decrease the time needed to boot the system.  <- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit

### Quick Boot

This allows BIOS to skip certain tests while booting. This will decrease the time needed to boot the system.

### Quiet Boot

When disabled, this displays normal POST messages. When enabled, this displays OEM Logo instead of POST messages.

### AddOn ROM Display Mode

This allows user to force BIOS/Option ROM of add-on cards to be displayed during quiet boot.

### Bootup Num-Lock

This select the power-on state for numlock.

### **PS/2 Mouse Support**

This select support for PS/2 mouse.

### **Wait for 'F1' If Error**

When set to Enabled, the system waits for the F1 key to be pressed when error occurs. This allows option ROM to trap interrupt 19.

### **Hit <DEL> Message Display**

This displays "Press <DEL> to run Setup" in POST.

### **Interrupt 19 Capture**

This allows option ROMs to trap interrupt 19.

## Security Settings

This setting comes with two options set the system password. Supervisor Password sets a password that will be used to protect the system and Setup utility. User Password sets a password that will be used exclusively on the system. To specify a password, highlight the type you want and press <Enter>. The Enter Password: message prompts on the screen. Type the password and press <Enter>. The system confirms your password by asking you to type it again. After setting a password, the screen automatically returns to the main screen.

To disable a password, just press the <Enter> key when you are prompted to enter the password. A message will confirm the password to be disabled. Once the password is disabled, the system will boot and you can enter Setup freely.

BIOS SETUP UTILITY						
Main	Advanced	PCIPnP	Boot	Security	Chipset	Exit
<b>Security Settings</b>				<b>Install or Change the Password.</b>		
Supervisor Password : Not Installed				<- Select Screen ↑↓ Select Item Enter Change F1 General Help F10 Save and Exit ESC Exit		
User Password : Not Installed						
<b>Change Supervisor Password</b> Change User Password						
Boot Sector Virus Protection [Disabled]						

## Advanced Chipset Settings

This setting configures the north bridge and south bridge settings.  
**WARNING!** Setting the wrong values may cause the system to malfunction.

BIOS SETUP UTILITY

Main	Advanced	PCIPnP	Boot	Security	Chipset	Exit
<b>Advanced Chipset Settings</b>					<b>Configure North Bridge features.</b>	
<p><b>WARNING:</b> Setting wrong values in below sections may cause system to malfunction.</p> <ul style="list-style-type: none"> <li>▶ North Bridge Configuration</li> <li>▶ South Bridge Configuration</li> </ul>					<p>&lt;- Select Screen                      ↑↓ Select Item                      Enter Go to Sub Screen                      F1 General Help                      F10 Save and Exit                      ESC Exit</p>	

BIOS SETUP UTILITY

Chipset	
<b>North Bridge Chipset Configuration</b>	<b>Options</b>
PCI MMIO Allocation: 4GB To 3072MB DRAM Frequency [Auto] Configure DRAM Timing by SPD [Enabled]	Enabled Disabled
Initiate Graphics Adapter [IGD] Internal Graphics Mode Select[Enabled, 8MB]	<- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
PEG Port Configuration ▶ Video Function Configuration	

### Configure DRAM Timing by SPD

When this item is enabled, the DRAM timing parameters are set according to the DRAM SPD (Serial Presence Detect). When disabled, you can manually set the DRAM timing parameters through the DRAM sub-items.

## Initiate Graphic Adapter

Select which graphics controller to use as the primary boot device. This option, by default, is set to IGD.

## Internal Graphics Mode Select

Use the feature to set the amount of system memory to be used by the Internal graphics device. expansion cards that require a specified area of memory to work properly.

Video Function Configuration		Options
<b>DVMT Mode Select</b>	<b>[DVMT Mode]</b>	<b>Fixed Mode</b> <b>DVMT Mode</b>  <- Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
DVMT/FIXED Memory	[256MB]	
Boot Display Device	[CRT]	
Flat Panel Type	[1024x768]	
Spread Spectrum Clock	[Disabled]	

## DVMT Mode Select

Select the control mode of memory built-in graphics capabilities. This option, by default, is set to DVMT Mode.

## DVMT/FIXED Memory

Sets the maximum memory size assigned to the integrated graphics capabilities. This option, by default, is set to 256MB.

## Boot Display Device

This option is used to select the display device used by the system when it boots.

## Flat Panel Type

This option is used to select the type of flat panel connected to the system.

Options include: 640x480 / 800x600 / 1024x768 / 800x480 / 1280x768 / 1280x800 / 1280x600.

## Spread Spectrum Clock

By default, this field is set to *Disabled*.

BIOS SETUP UTILITY

Main	Advanced	PCIPnP	Boot	Security	Chipset	Exit
<b>South Bridge Chipset Configuration</b>					<b>Options</b>	
<b>USB Function</b> [10 USB Ports]					Disabled	
USB 2.0 Controller [Enabled]					2 USB Ports	
HAD Controller [Enabled]					4 USB Ports	
SMBUS Controller [Enabled]					6 USB Ports	
					8 USB Ports	
					10 USB Ports	
PCIE Ports Configuration					<- Select Screen	
PCIE Port 0 [Auto]					↑↓ Select Item	
PCIE Port 1 [Auto]					+ - Change Option	
PCIE Port 2 [Auto]					F1 General Help	
PCIE Port 3 [Auto]					F10 Save and Exit	
PCIE Port 4 [Auto]					ESC Exit	
PCIE Port 5 [Auto]						
PCIE High Priority Port [Disabled]						
PCIE Port 0 IOxAPIC Enable [Disabled]						
PCIE Port 1 IOxAPIC Enable [Disabled]						
PCIE Port 2 IOxAPIC Enable [Disabled]						
PCIE Port 3 IOxAPIC Enable [Disabled]						
PCIE Port 4 IOxAPIC Enable [Disabled]						
PCIE Port 5 IOxAPIC Enable [Disabled]						
Enable Onboard PCI option ROM [Disabled]						

**USB Function**

This option enables the number of USB ports desired or disables the USB function.

**USB 2.0 Controller**

This option is disabled by default.

**HDA Controller**

This option is used to enable the Southbridge high definition audio controller.

**SMBUS Controller**

This option is enabled by default.

**Clock-Gen Spectrum**

This option is disabled by default.

**Enable Onboard PCI option ROM**

This option is disabled by default.

## Exit Setup

The exit setup has the following settings which are:

BIOS SETUP UTILITY						
Main	Advanced	PCI/PnP	Boot	Security	Chipset	Exit
<b>Exit Options</b>					Exit system setup after saving the changes.	
<b>Save Changes and Exit</b> Discard Changes and Exit Discard Changes  Load Optimal Defaults Load Failsafe Defaults					<b>F10 key can be used for this operation</b>  <b>&lt;- Select Screen</b> <b>↑↓ Select Item</b> <b>Enter Go to Sub Screen</b> <b>F1 General Help</b> <b>F10 Save and Exit</b> <b>ESC Exit</b>	

### Save Changes and Exit

This option allows you to determine whether or not to accept the modifications and save all changes into the CMOS memory before exit.

### Discard Changes and Exit

This option allows you to exit the Setup utility without saving the changes you have made in this session.

### Discard Changes

This option allows you to discard all the changes that you have made in this session.

### Load Optimal Defaults

This option allows you to load the default values to your system configuration. These default settings are optimal and enable all high performance features.

### Load Failsafe Defaults

This option allows you to load the troubleshooting default values permanently stored in the BIOS ROM. These default settings are non-optimal and disable all high-performance features.

This page is intentionally left blank.

## Drivers Installation

This section describes the installation procedures for software and drivers under the Windows XP, Windows Vista and Windows 7. The software and drivers are included with the motherboard. If you find the items missing, please contact the vendor where you made the purchase. The contents of this section include the following:

Intel Chipset Software Installation Utility .....	38
Intel Pineview Chipset Family Graphics Driver Installation.....	40
Realtek High Definition Codec Audio Driver Installation .....	42
Intel 82583V LAN Drivers Installation.....	43


### **IMPORTANT NOTE:**

After installing your Windows operating system (Windows XP/ Vista/ 7), you must install first the Intel Chipset Software Installation Utility before proceeding with the drivers installation.

## Intel Chipset Software Installation Utility

The Intel Chipset Drivers should be installed first before the software drivers to enable Plug & Play INF support for Intel chipset components. Follow the instructions below to complete the installation under Windows XP/Vista/7.

1. Insert the drivers DVD into the DVD drive. Click **Intel** and then **Intel(R) Pineview Chipset Drivers**. Click **Intel(R) Chipset Software Installation Utility**.



2. When the welcome screen to the Intel(R) Chipset Software Installation Utility appears, click **Next** to continue.



3. Click **Yes** to accept the software license agreement and proceed with the installation process.
4. On the Readme Information screen, click **Next** to continue. When the Setup Progress screen appears, click **Next** to continue.




5. The Setup process is now complete. Click **Finish** to restart the computer and for changes to take effect.



## Intel Pineview Chipset Family Graphics Driver Installation

To install the VGA drivers, follow the steps below to proceed with the installation.


1. Insert the drivers DVD into the DVD drive. Click **Intel** and then **Intel(R) Pineview Chipset Drivers**. Click **Intel(R) Pineview Chipset Family Graphics Driver**.



2. When the welcome screen of the Intel(R) Graphics Media Accelerator Driver appears, click **Next** to continue.




3. Click **Yes** to agree with the license agreement and continue the installation.



4. Click **Next** in the Readme File Information window.

5. Click **Next** in the Setup Progress window.




6. Setup is now complete. Click **Finish** to restart the computer and for changes to take effect.

## Realtek High Definition Codec Audio Driver Installation

---

Follow the steps below to install the Realtek HD Codec Audio Drivers.

1. Insert the drivers DVD into the DVD drive. Click **Intel** and then **Intel(R) Pineview Chipset Drivers**. Click **Realtek High Definition Codec Audio Driver**.



2. When the welcome screen to InstallShield Wizard for **Realtek High Definition Audio Driver** appears, click **Next** to start the installation.

3. When the InstallShield Wizard has finished performing maintenance operations on Realtek High Definition Codec Audio Driver, click **Finish** to restart the computer.


---

## Intel 82583V LAN Drivers Installation

---

Follow the steps below to install Intel 82583V LAN Drivers.

1. Insert the drivers DVD into the DVD drive. Click **LAN Card** and then **Intel LAN Controller Drivers**. Click **Intel (R)Gigabit Ethernet Drivers**.



2. On the next screen, click **Install Drivers** to start the drivers installation.

3. When the Welcome screen appears, click **Next** to continue.

4. In the License Agreement screen, click **I accept the terms in license agreement** and **Next** to accept the software license agreement and proceed with the installation process.

5. When the Setup Options appears, click **Install Drivers only** and **Next** to continue.

6. When the Ready to Install the Program screen appears, click **Install** to continue.

7. The Setup process is now complete (InstallShield Wizard Completed). Click **Finish** to restart the computer and for changes to take effect.

This page is intentionally left blank.

# Appendix

## A. I/O Port Address Map

Each peripheral device in the system is assigned a set of I/O port addresses that also becomes the identity of the device. The following table lists the I/O port addresses used.

Address	Device Description
0000h-0CF7h	PCI bus
0000h-0CF7h	Direct memory access controller
0010h-001Fh	Motherboard resources
0020h-0021h	Programmable interrupt controller
0022h-003Fh	Motherboard resources
0040h-0043h	System timer
0044h-005Fh	Motherboard resources
0060h-0060h	Motherboard resources
0061h-0061h	System speaker
0062h-0063h	Motherboard resources
0064h-0064h	Motherboard resources
0065h-006Fh	Motherboard resources
0070h-0071h	System CMOS/real time clock
0072h-007Fh	Motherboard resources
0080h-0080h	Motherboard resources
0081h-0083h	Direct memory access controller
0084h-0086h	Motherboard resources
0087h-0087h	Direct memory access controller
0088h-0088h	Motherboard resources
0089h-008Bh	Direct memory access controller
008Ch-008Eh	Motherboard resources
008Fh-008Fh	Direct memory access controller
0090h-009Fh	Motherboard resources
00A0h-00A1h	Programmable interrupt controller
00A2h-00BFh	Motherboard resources
00C0h-00DFh	Direct memory access controller
00E0h-00EFh	Motherboard resources
00F0h-00FFh	Numeric data processor
01F0h-01F7h	Primary IDE Channel
0274h-0277h	ISAPNP Read Data Port
0279h-0279h	ISAPNP Read Data Port

Address	Device Description
02E8h-02EFh	Communications Port (COM4)
02F8h-02FFh	Communications Port (COM2)
03B0h-03BBh	Intel(R) Graphics Media Accelerator 3150
03C0h-03DFh	Intel(R) Graphics Media Accelerator 3150
03E8h-03EFh	Communications Port (COM3)
03F6h-03F6h	Primary IDE Channel
03F8h-03FFh	Communications Port (COM1)
0400h-041Fh	Intel(R) ICH8 Family SMBus Controller - 283E
04D0h-04D1h	Motherboard resources
0500h-053Fh	Motherboard resources
0800h-087Fh	Motherboard resources
0A00h-0A0Fh	Motherboard resources
0A10h-0A1Fh	Motherboard resources
0A79h-0A79h	ISAPNP Read Data Port
0D00h-FFFFh	PCI bus
B480h-B48Fh	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
B800h-B80Fh	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
B880h-B883h	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
BC00h-BC07h	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
C000h-C003h	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
C080h-C087h	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
C400h-C41Fh	Standard Universal PCI to USB Host Controller
C480h-C49Fh	Intel(R) ICH8 Family USB Universal Host Controller - 2832
C800h-C81Fh	Intel(R) ICH8 Family USB Universal Host Controller - 2831
C880h-C89Fh	Intel(R) ICH8 Family USB Universal Host Controller - 2830

---

Address	Device Description
CC00h-CC07h	Intel(R) Graphics Media Accelerator 3150
D000h-DFFFh	Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
D800h-D8FFh	Realtek PCIe GBE Family Controller
E000h-EFFFh	Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
E800h-E8FFh	Realtek PCIe GBE Family Controller #2
FFA0h-FFAFh	Intel(R) ICH8M Ultra ATA Storage Controllers - 2850

## B. Interrupt Request Lines (IRQ)

Peripheral devices use interrupt request lines to notify CPU for the service required. The following table shows the IRQ used by the devices on board.

Level	Function
IRQ0	System timer
IRQ1	PS/2 Keyboard
IRQ3	Communications Port (COM2)
IRQ4	Communications Port (COM1)
IRQ5	Intel(R) ICH8 Family SMBus Controller - 283E
IRQ8	System CMOS/real time clock
IRQ9	Microsoft ACPI-Compliant System
IRQ10	Communications Port (COM4)
IRQ11	Communications Port (COM3)
IRQ12	PS/2 Mouse
IRQ13	Numeric data processor
IRQ14	Primary IDE Channel
IRQ16	Intel(R) Graphics Media Accelerator 3150
IRQ16	Realtek PCIe GBE Family Controller
IRQ16	Standard Universal PCI to USB Host Controller
IRQ17	Realtek PCIe GBE Family Controller #2
IRQ18	Intel(R) ICH8 Family USB Universal Host Controller - 2832
IRQ18	Intel(R) ICH8M 3 port Serial ATA Storage Controller - 2828
IRQ19	Intel(R) ICH8 Family USB Universal Host Controller - 2831
IRQ21	Microsoft UAA Bus Driver for High Definition Audio
IRQ22	Intel(R) ICH8 Family PCI Express Root Port 1 - 283F
IRQ22	Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
IRQ23	Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
IRQ23	Intel(R) ICH8 Family USB Universal Host Controller - 2830
IRQ23	Intel(R) ICH8 Family USB2 Enhanced Host Controller - 2836

## C. Watchdog Timer Configuration

The WDT is used to generate a variety of output signals after a user programmable count. The WDT is suitable for use in the prevention of system lock-up, such as when software becomes trapped in a deadlock. Under these sorts of circumstances, the timer will count to zero and the selected outputs will be driven. Under normal circumstance, the user will restart the WDT at regular intervals before the timer counts to zero.

### SAMPLE CODE:

```
File of the W627UHG.CPP
//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#include "W627UHG.H"
#include <dos.h>
//-----
unsigned int W627UHG_BASE;
void Unlock_W627UHG (void);
void Lock_W627UHG (void);
//-----
unsigned int Init_W627UHG(void)
{
    unsigned int result;
    unsigned char ucDid;

    W627UHG_BASE = 0x4E;
    result = W627UHG_BASE;

    ucDid = Get_W627UHG_Reg(0x20);
    if (ucDid == 0xA2)                                //W83627UHG??
    {    goto Init_Finish; }

    W627UHG_BASE = 0x2E;
    result = W627UHG_BASE;

    ucDid = Get_W627UHG_Reg(0x20);
    if (ucDid == 0xA2)                                //W83627UHG??
    {    goto Init_Finish; }

    W627UHG_BASE = 0x00;
    result = W627UHG_BASE;

Init_Finish:
    return (result);
}
//-----
void Unlock_W627UHG (void)
```

```
{
    outportb(W627UHG_INDEX_PORT, W627UHG_UNLOCK);
    outportb(W627UHG_INDEX_PORT, W627UHG_UNLOCK);
}
//-----
void Lock_W627UHG (void)
{
    outportb(W627UHG_INDEX_PORT, W627UHG_LOCK);
}
//-----
void Set_W627UHG_LD( unsigned char LD)
{
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, W627UHG_REG_LD);
    outportb(W627UHG_DATA_PORT, LD);
    Lock_W627UHG();
}
//-----
void Set_W627UHG_Reg( unsigned char REG, unsigned char DATA)
{
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, REG);
    outportb(W627UHG_DATA_PORT, DATA);
    Lock_W627UHG();
}
//-----
unsigned char Get_W627UHG_Reg(unsigned char REG)
{
    unsigned char Result;
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, REG);
    Result = inportb(W627UHG_DATA_PORT);
    Lock_W627UHG();
    return Result;
}
//-----
```

---

File of the W627UHG.H

```
//-----  
//  
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY  
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE  
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR  
// PURPOSE.  
//  
//-----  
#ifndef __W627UHG_H  
#define __W627UHG_H          1  
//-----  
#define W627UHG_INDEX_PORT (W627UHG_BASE)  
#define W627UHG_DATA_PORT  (W627UHG_BASE+1)  
//-----  
#define W627UHG_REG_LD      0x07  
//-----  
#define W627UHG_UNLOCK     0x87  
#define W627UHG_LOCK       0xAA  
//-----  
unsigned int Init_W627UHG(void);  
void Set_W627UHG_LD( unsigned char);  
void Set_W627UHG_Reg( unsigned char, unsigned char);  
unsigned char Get_W627UHG_Reg( unsigned char);  
//-----  
#endif    // __W627UHG_H
```

## APPENDIX

---

File of the MAIN.CPP

```
//-----  
//  
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY  
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE  
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR  
// PURPOSE.  
//  
//-----  
#include <dos.h>  
#include <conio.h>  
#include <stdio.h>  
#include <stdlib.h>  
#include "W627UHG.H"  
//-----  
int main (void);  
  
void WDTInitial(void);  
void WDTEnable(unsigned char);  
void WDTDisable(void);  
  
//-----  
int main (void)  
{  
    char SIO;  
  
    SIO = Init_W627UHG();  
    if (SIO == 0)  
    {  
        .....printf("Can not detect Winbond 83627UHG, program abort.\n");  
        .....return(1);  
    }  
  
    WDTInitial();  
  
    WDTEnable(10);  
  
    WDTDisable();  
  
    return 0;  
}  
//-----  
void WDTInitial(void)  
{  
    unsigned char bBuf;  
    Set_W627UHG_LD(0x08);.....//switch to logic device 8  
    bBuf = Get_W627UHG_Reg(0x30);  
    bBuf &= (~0x01);  
    Set_W627UHG_Reg(0x30, bBuf);.....//Enable WDTO  
}  
//-----  
void WDTEnable(unsigned char NewInterval)  
{  
    unsigned char bBuf;  
  
    Set_W627UHG_LD(0x08);.....  
    Set_W627UHG_Reg(0x30, 0x01); .....//enable timer
```

```
bBuf = Get_W627UHG_Reg(0xF5);
bBuf &= (~0x08);
Set_W627UHG_Reg(0xF5, bBuf);.....//count mode is second

Set_W627UHG_Reg(0xF6, NewInterval);.....//set timer
}
//-----
void WDTDisable(void)
{
    Set_W627UHG_LD(0x08);.....
    Set_W627UHG_Reg(0xF6, 0x00);.....//clear watchdog timer
    Set_W627UHG_Reg(0x30, 0x00);.....
}
//-----
```

## D. Digital I/O Sample Code

File of the W627UHG.H

```
//-----  
//  
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY  
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE  
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR  
// PURPOSE.  
//  
//-----  
#ifndef __W627UHG_H  
#define __W627UHG_H 1  
//-----  
#define W627UHG_INDEX_PORT (W627UHG_BASE)  
#define W627UHG_DATA_PORT (W627UHG_BASE+1)  
//-----  
#define W627UHG_REG_LD 0x07  
//-----  
#define W627UHG_UNLOCK 0x87  
#define W627UHG_LOCK 0xAA  
//-----  
unsigned int Init_W627UHG(void);  
void Set_W627UHG_LD( unsigned char);  
void Set_W627UHG_Reg( unsigned char, unsigned char);  
unsigned char Get_W627UHG_Reg( unsigned char);  
//-----  
#endif // __W627UHG_H
```

File of the W627UHG.CPP

```
//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#include "W627UHG.H"
#include <dos.h>
//-----
unsigned int W627UHG_BASE;
void Unlock_W627UHG (void);
void Lock_W627UHG (void);
//-----
unsigned int Init_W627UHG(void)
{
    unsigned int result;
    unsigned char ucDid;

    W627UHG_BASE = 0x4E;
    result = W627UHG_BASE;

    ucDid = Get_W627UHG_Reg(0x20);
    if (ucDid == 0xA2)                                //W83627UHG??
    {
        goto Init_Finish;
    }

    W627UHG_BASE = 0x2E;
    result = W627UHG_BASE;

    ucDid = Get_W627UHG_Reg(0x20);
    if (ucDid == 0xA2)                                //W83627UHG??
    {
        goto Init_Finish;
    }

    W627UHG_BASE = 0x00;
    result = W627UHG_BASE;

Init_Finish:
    return (result);
}
//-----
void Unlock_W627UHG (void)
{
    outportb(W627UHG_INDEX_PORT, W627UHG_UNLOCK);
    outportb(W627UHG_INDEX_PORT, W627UHG_UNLOCK);
}
//-----
void Lock_W627UHG (void)
{
    outportb(W627UHG_INDEX_PORT, W627UHG_LOCK);
}
//-----
void Set_W627UHG_LD( unsigned char LD)
```

```
{
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, W627UHG_REG_LD);
    outportb(W627UHG_DATA_PORT, LD);
    Lock_W627UHG();
}
//-----
void Set_W627UHG_Reg( unsigned char REG, unsigned char DATA)
{
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, REG);
    outportb(W627UHG_DATA_PORT, DATA);
    Lock_W627UHG();
}
//-----
unsigned char Get_W627UHG_Reg(unsigned char REG)
{
    unsigned char Result;
    Unlock_W627UHG();
    outportb(W627UHG_INDEX_PORT, REG);
    Result = inportb(W627UHG_DATA_PORT);
    Lock_W627UHG();
    return Result;
}
//-----
```

File of the MAIN.CPP

```
//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#include <dos.h>
#include <conio.h>
#include <stdio.h>
#include <stdlib.h>
#include "W627UHG.H"
//-----
int main (void);

void Dio5Initial(void);
void Dio5SetOutput(unsigned char);
unsigned char Dio5GetInput(void);
void Dio5SetDirection(unsigned char);
unsigned char Dio5GetDirection(void);
//-----
int main (void)
{
    char SIO;

    SIO = Init_W627UHG();
    if (SIO == 0)
    {
        printf("Can not detect Winbond 83627UHG, program abort.\n");
        return(1);
    }

    Dio5Initial();

    //for GPIO50..57
    Dio5SetDirection(0x0F);//GP50..53 = input, GP54..57=output
    printf("Current DIO direction = 0x%X\n", Dio5GetDirection());

    printf("Current DIO status = 0x%X\n", Dio5GetInput());

    printf("Set DIO output to high\n");
    Dio5SetOutput(0x0F);

    printf("Set DIO output to low\n");
    Dio5SetOutput(0x00);

    return 0;
}
```

```
}
//-----
void Dio5Initial(void)
{
    unsigned char ucBuf;

    Set_W627UHG_LD(0x08); //switch to logic device 8
    //enable the GP5 group
    ucBuf = Get_W627UHG_Reg(0x30);
    ucBuf |= 0x02;
    Set_W627UHG_Reg(0x30, ucBuf);
}
//-----
void Dio5SetOutput(unsigned char NewData)
{
    Set_W627UHG_LD(0x08); //switch to logic device 8
    Set_W627UHG_Reg(0xE1, NewData);
}
//-----
unsigned char Dio5GetInput(void)
{
    unsigned char result;

    Set_W627UHG_LD(0x08); //switch to logic device 8
    result = Get_W627UHG_Reg(0xE1);
    return (result);
}
//-----
void Dio5SetDirection(unsigned char NewData)
{
    //NewData : 1 for input, 0 for output
    Set_W627UHG_LD(0x08); //switch to logic device 8
    Set_W627UHG_Reg(0xE0, NewData);
}
//-----
unsigned char Dio5GetDirection(void)
{
    unsigned char result;

    Set_W627UHG_LD(0x08); //switch to logic device 8
    result = Get_W627UHG_Reg(0xE0);
    return (result);
}
//-----
```