



Features

- Fanless and thin low power system design w/ IBASE IB888-11-ASB single board computer
- Onboard Intel® Atom™ processors (Z510P), 1.1GHz
- 6x USB in front/ rear panel for easy connection
- Rear panel reserved one wireless antenna jack
- PCI-E(x1) slot reserved for wireless module expansions
- DVI/ LAN/ CF and power button in front panel
- DC-in power input

Specifications

System Mainboard	IB888-11-ASB
CPU Type	Intel® Atom™ Processors (Z510P)
System Speed	1.1GHz
Memory	1x DDR2 SO-DIMM, Max. 2GB
Construction	Steel
Chassis Color	Black
Front Panel External I/O	1x CF socket slot w/ ejector, 4x USB 2.0, 1x COM
Rear Panel External I/O	2x USB 2.0, 1x RJ-45, 1x COM, 1x DVI-D, DC-in jack, 1x power button with LED, 1x antenna mounting hole
Storage	1x Type II CF socket
Power Supply	60W power adaptor
Mounting	Desktop or VESA mount (75mm x 75mm)
Dimensions	190mm(W) x 132mm(D) x 30mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CSB200-88811M	Fanless chassis with IB888-11-ASB 3.5-inch SBC, w/ external CF card slot, 60W power adaptor
---------------	---

Features

- Fanless System supports IBASE IB883 3.5" Disk Size SBC
- Onboard Intel® Atom™ Processor N270, 1.6GHz
- Aluminum & steel chassis available in black color
- One 2.5" HDD drive bay
- Rear panel I/O for USB, DVI, KB/MS, LAN and DC-in jack
- Wall mount kit supported

Specifications

System Mainboard	IB883
CPU Type	Intel® Atom™ Processor N270
System Speed	1.6GHz
Memory	1x DDR2 533 SO-DIMM, Max. 2GB
Construction	Aluminum & Steel
Chassis Color	Black
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, audio, 2x USB ports
Rear Panel External I/O	1x DVI, 1x VGA, 2x USB ports, 2x COM ports, 2x RJ45 connectors, KB/MS connector, DC-in jack
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Desktop or wall mount
Dimensions	172mm(W) x 113.6mm(D) x 52mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

CSB200-883M	Fanless Chassis with IB883 3.5" SBC, w/ 2.5" HDD holder, 60W Power Adaptor, (RoHS), mounting brackets
-------------	---

- 1 eFlex Platform
- 2 Motherboards
- 3 Disk-Size SBCs
- 4 CPU Modules
- 5 PC/104 Plus
- 6 CPU Cards
- 7 Embedded Systems
- 8 Network Security Appliance