

FWA6204



Features

- Supports Intel® Celeron® M or Pentium® M processors, up to 2GHz, 400MHz FSB
- DDR DIMM x 2, up to 2GB
- Supports 4x Intel® Gigabit LAN
- Supports 1x 3.5" SATA hard disk storage
- Optional 16x2 LCM for ease of control and operation
- RoHS compliant

Specifications

| | |
|----------------|--|
| CPU | Intel® Celeron® M 600MHz onboard or Intel® Pentium® M / Celeron® M, up to 2GHz, 400MHz FSB |
| Chipset | Intel® 852GM / ICH4 |
| Memory | 2x 184-pin DDR DIMM, up to 2GB DDR266 |
| Network | 4x Intel® 82541PI Gigabit LAN Hardware Bypass on Eth 0 & 1 |
| Expansion Slot | 2x PCI slots, 1x Mini-PCI socket |
| Storage | 1x Internal HDD bay for 3.5" SATA hard disk Onboard Type II CF socket |
| USB | 2x USB 2.0 ports on front panel Pin headers for 2x ports |
| Serial I/O | 1x DB-9 console connector on front panel Pin header for 2x COM ports |
| VGA | Pin header on board |
| LCM | Optional 2x16 characters LCM module |
| LED | Power/HDD/Status/Alarm indication LEDs |
| Power Supply | Full range 200W ATX with PFC PSU |
| Dimensions | 44mm (H) x 430mm (W) x 311mm (D) |

Environmental

| | |
|-----------------------|------------|
| Operating Temperature | 0 ~ 45°C |
| Storage Temperature | -20 ~ 70°C |
| Operating Humidity | 5% ~ 95% |
| Certification | CE/FCC |

Ordering Information

| | |
|---------------|--|
| FWA6204-040V | Entry Level, Intel® Celeron® M 600MHz with 512K cache, 4x Gigabit LAN, with LAN bypass, w/ LCM |
| FWA6204S-040V | Entry Level, socket 479, 4x Gigabit LAN, with LAN bypass, w/ LCM |
| VGA4 | VGA cable |
| PS2D | PS/2 Keyboard and Mouse Cable |
| MB875S-R | Socket 479 852GM Custom-size motherboard for FWA6204S-040V, with VGA and 4x Gigabit LAN |
| MB875-600-R | Celeron® M 600MHz / 512K 852GM Custom-size motherboard for FWA6204-040V, with VGA and 4x Gigabit LAN |



Remarks:

* Specifications are subject to change without prior notice.

- 1 Motherboards
- 2 Disk-Size SBGA
- 3 CPU Modules
- 4 PC/104 Pulse
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance