

IPPD1560RF

Heavy-duty Industrial Monitor

15.6" 1920 x 1080 VGA/AUDIO/ DVI/RFID Monitor



Features

- Flat Panel Design
- Projected Capacitive Touch
- Multiple signal interfaces with VGA & DVI
- Built-in 13.56 MHz RFID reader
- Supports 1920 x 1080 front web camera
- OSD Keypad Control at top side
- DC 12V Power Input



Specifications

| | | |
|------------------------|-------------------------|---|
| Display & Touch Screen | Display Size | 15.6" TFT-LCD |
| | Max. Resolution | 1920 x 1080 |
| | Luminance (cd/m2) | 300 |
| | Contrast | 700:1 |
| | Max. Color | 262K |
| | View Angle (H/V) | 178/178 |
| | Backlight Lifetime(hrs) | 15000 |
| | Touch Type | Projected capacitive |
| | Touch Interface | USB |
| | Light Transmission (%) | 90% |
| External I/O Port | Point of touch | 10 |
| | Signal input | VGA/DVI |
| | USB | 1x USB for touch/RFID/camera 1x USB Hub |
| | Audio | 1x Audio |
| Mechanical | Power Connector | Power jack |
| | Dimensions (mm) | 397.7 x 287 x 45 |
| System | Net Weight (kgs) | 4.5 |
| | Membrane Control | Menu/Enter, Left/Up, Right/Down, Power on/off |
| | RFID | 1x 13.56 MHz RFID Reader |
| | Built-in Camera | 1x 1920 x 1080 front web camera |
| | Built-in Speaker/Mic | 2x Speaker |
| Power | Power Input Range | 12V DC Input |
| Construction | Chassis Material | SGCC |
| | Color (Front/Back) | Black |
| | IP Rating | IP65 front bezel |
| | Mounting | VESA 75x75, 100x100 mm |
| Environmental | Operating Temperature | 0°C~50°C |
| | Storage Temperature | -20°C~60°C |
| | Storage Humidity | 10%~90% (non-condensing) |
| | Certification | CE/FCC Class-A |

Ordering Information

IPPD1560RF

15.6" FHD Flat Panel Design Monitor, projected capacitive touch, VGA, DVI, Audio, OSD keypad, camera and RFID reader, 12V DC power input with power adapter

Dimensions

