

FWA5104

Desktop Network Appliance

Compact & Slim Fanless Network Appliance with AMD Embedded G-series SoC & 4 GbE Ports



Specifications

CPU	AMD Embedded G-series SoC, up to 1.2GHz
Chipset	N/A
Memory	1x DDR3L SO-DIMM up to 1600MHz, Max. 8GB (Non-ECC)
Display	SoC Integrated (optional) 1x mini DisplayPort (optional)
Ethernet	4x Intel® I211-AT GbE
Bypass	1x segment, LAN 3/4
Expansion	1x half-size Mini PCI-E (PCIe & SATA signal)
IPMI	N/A
Storage	1x 2.5" SATA SSD drive bay 1x SATA-III CFast socket
TPM	N/A
I/O	3x LED (Power / HDD / Status) 1x Factory default button (GPIO) 1x RJ45 console 2x USB 3.0 1x USB 2.0
Power Supply	Full range 40W power adaptor / 12V
Dimensions	187.5mm (W) x 116mm (D) x 42mm (H) 7.38"(W) x 4.57"(D) x 1.65"(H)
Weight	1.6 kg (3.53 lbs)
Operating Temperature	HDD: 0°C ~ 40°C (32°F ~ 104°F) SSD: 0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20° ~ 70°C (-4°F ~ 158°F)
Operating Humidity	5% ~ 90%
Certification	CE/FCC

Features

- 2nd Gen AMD Embedded G-series SoC
- 1x DDR3L SO-DIMM, Max. 8GB
- 4x Intel® I211-AT GbE ports, with one Bypass segment
- Integrated with a Crypto Coprocessor
- 2x USB 3.0, 1x USB 2.0, 1x COM, 1x SATA III
- 1x CFast socket, 1x Mini PCI-E slot
- 1x Mini DisplayPort (FWA5104-4CG)

Ordering Information

FWA5104-4CG	Desktop Appliance, AMD GX-412HC, 1x DDR3L SO-DIMM, 4x GbE, 40W Adaptor, CPU Cooler, Mini DisplayPort, 2.5" HDD bracket, Barebone without RAM/HDD
FWA5104-4C	Desktop Appliance, AMD GX-412TC, 1x DDR3L SO-DIMM, 4x GbE, 40W Adaptor, CPU Cooler, 2.5" HDD bracket, Barebone without RAM/HDD
PK1-51	Console cable, 160cm

Dimensions

