



Features

- iSMART - for Auto-scheduler and power resume
- Supports 2nd/3rd Generation Intel® Core™ i7/i5/i3/ Celeron® QC/DC Processors
- 2x DDR3 SO-DIMM, Max. 16GB
- Intel® HD Graphics Engine
- iAMT compliance for remote management
- 2x USB 3.0 ports
- 2x Mini PCI-E(x1) slot for Wi-Fi, 4G and TV tuner options
- Compact design

Specifications

System Mainboard	IB902A
CPU Type	2nd/3rd Generation Intel® Mobile Core™ i7/i5/i3/ Celeron® QC/ DC processors (TDP <= 35W)
CPU Socket	rPGA988B
Chipset	Intel® QM77
Memory	2x DDR3 1066/1333/1600 MHz SO-DIMM, Max. 16GB (Non-ECC)
Graphics	Intel® HD graphics supports: OpenGL 3.0 DirectX® 11 OpenCL 1.1 MFX Hardware Video Decoder – MPEG-2, AVC, VC-1, JPEG
LAN	1x Intel® 82579LM Gigabit LAN controller with iAMT 9.0
Expansion Slots	Mini PCI-E(x1) for Wi-Fi + Bluetooth and 4G and TV tuner options, 1x Expresscard slot for 4G module
I/O Interface	1x HDMI, 1x DVI-I 1x Microjack audio connectors for Line-out 1x Gigabit LAN 2x USB 3.0, 1x RS-232 (RJ45 connector) 1x Power button with LED light 1x DC jack
Auto Control and Monitoring	Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/min)
Power Requirement	+12V DC-in
Construction	SGCC
Weight	1 kg (2.20lbs)
Chassis Color	Black & white
Storage	1x mSATA 1x SATA 3.0 2.5" HDD Dock
Power Supply	60W power adaptor
Mounting	Standard system bracket
Dimensions	178mm(W) x 150mm(D) x 35mm(H) 7.01"(W) x 5.91"(D) x 1.38"(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	mSATA: 5 grms / 5~500Hz / random operation
Certification	CE, FCC, cULus, CCC

Ordering Information

SI-62	Signage Player with Intel® Core™ i5-3610ME processor (3M Cache, up to 3.30 GHz) 2x 2GB DDR3 SO-DIMM Memory, 2.5" 320GB SATA HDD, 60W power adaptor
SI-MK3	Mounting bracket for SI-32-N/38/62/83 series

Dimensions

