



Features

- iSMART - for auto-scheduler and power resume
- Supports up to four display outputs
- Discrete AMD Radeon™ E6760 graphics processors (480 processing elements) with 1024MB GDDR5-1600 graphics memory
- Supports 3rd Generation Intel® Core™ i7/i5/i3, Pentium QC/DC desktop processors
- 2x DDR3 1600MHz SO-DIMM, Max. 16GB
- 2x Mini PCI-E (x1) slots for Wi-Fi, 4G and TV tuner options
- 2x RS232 serial ports

Specifications

| | |
|-----------------------------|--|
| System Mainboard | IB964 |
| CPU Type | 3rd Generation Intel® Core™ i7/i5/i3, Pentium QC/DC Desktop Processors *The maximum TDP supported 77W |
| CPU Socket | LGA1155 |
| Chipset | Intel® Q77 |
| Memory | 2x DDR3 1600MHz DIMM, Max. 16GB (Non-ECC) |
| Graphics | AMD E6760 GPU (480 Cores @ 600 MHz; 31W) with 1024MB GDDR5-1600 (57.6 GB/s) 128-bit wide, 1.DirectX®11GB GDDR5, 51.2 GB/s DirectX®11, Shader 5.0, OpenGL 4.1 capable UVD3 video & display engines for HD, Blu-ray & 3D |
| LAN | 1x Intel® 82579LM Gigabit LAN controller (with iAMT 8.0) 1x Intel® 82579V Gigabit LAN controller |
| Expansion Slots | 2x Mini PCI-E (x1) slot for Wi-Fi, 4G and TV tuner options |
| I/O Interface | 3x DVI, 1x Hybrid DVI (DVI/ VGA / HDMI with audio) 2x USB 2.0 ports, 2x USB 3.0 ports 2x RJ45 for LAN, 2x RJ45 for RS232 2x Microjack audio connectors for Line-in / Line-out Power / HDD LED, 1x Power on/off button 1x AC power inlet |
| Auto Control and Monitoring | Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/min) |
| Power Requirement | AC-in |
| Construction | SGCC |
| Weight | 4.1kg (9.04lbs) |
| Chassis Color | Black & white |
| Storage | 1x mSATA 1x SATA 3.0 2.5" HDD Dock |
| Power Supply | Internal 250w PSU |
| Mounting | Standard system bracket |
| Dimensions | 380mm(W) x 250mm(D) x 45mm(H) 14.96"(W) x 9.84"(D) x 1.77"(H) |
| Operating Temperature | 0°C~ 45°C (32°F~113°F) |
| Storage Temperature | -20°C ~ 80°C (-4°F~176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | mSATA: 5 grms / 5~500Hz / random operation |
| Certification | CE, FCC class B, cULus & CCC |
| Operating System | Windows XP, Win7 32/64-bit, Win8 64-bit, Win8.1 64-bit Win10 64-bit Enterprise (Upgrade Only) |

Ordering Information

| | |
|-------|---|
| SI-64 | Signage Player with 3rd Generation Intel® Core™ i5 (DT) i5-3550S Processors (6M Cache, up to 3.0 GHz) with AMD E6760 GPU, 2x 4GB DDR3 DIMM, 2.5" 320GB SATA HDD |
|-------|---|

Dimensions

